

SEALEY

Sealey Refrigeration International Limited mainly specializes in designing and manufacturing refrigeration and ventilation equipment, own "Sealey" trademark. We can supply elevator air conditioner, AC/DC dual power solar air conditioner and normal air conditioner. Our products have passed ISO9001 international quality management system, CCC and CE certificate.


Our factory has the first-class producing and testing equipments. With good quality, our air conditioner is recognized by the national quality and technical inspection quarantine bureau and once again won the certificate for the products exemption from quality surveillance. Besides, we have passed CCECS and been authorized "Contract-observing and trust-worthy unit " by industry and commerce administration.

Sealey elevator air conditioner adopt advanced technology, has got patent certificate. We have cooperated with elevator companies of Otis, Toshiba, Hyundai, Sanyo, etc, exported to Australia, Bahrain, Kuwait, Qatar, Mexico, UAE, Iraq, India, Nigeria and so on.



◎ 特点 Characteristics

1. The inner parts are made of stainless steel, corrosion resistance, product lifetime is ten years.
2. Adopt Japanese Hitachi compressor, hydrophilic aluminum fin, internal thread tube.
3. The functions include cooling, heating, ventilation, dehumidification, timing on/off, auto-restart.
4. Adopt spraying & evaporation technology, the condensed water can evaporate automatically.
5. Use wireless remote control, LCD display, automatic fault diagnosis.
6. Current overload protector for compressor, motor and other electrical parts.
7. Ceramic PTC heater with overheat protection device (Optional)
8. Installation and maintenance are simple.



◎ 规格 Specification

Model			KC(R)-20/DT	KC(R)-25/DT-A
Power supply			220V-240V/50HZ/1PH	
Refrigerant			R22	R410A
Nominal capacity	Cooling	W	2000	2500
	Heating	W	2000	2000
Rated input power	Cooling	W	760	950
	Heating	W	2000	2000
Rated current	Cooling	A	3.5	4.4
	Heating	A	9.1	9.1
Air circulation		M ³ /h	400	400
Noise in lift car		db(A)	≤45	≤48
Elevator air conditioner noise		db(A)	≤52	≤53
Machine dimension	Net	mm	546*462*396	546*462*396
	Packing	mm	600*520*480	600*520*480
Machine weight	Net	kg	36	38
	Gross	kg	38	40
Suitable Elevator Load Capacity(kg)			<1350	≥1350
Accessory packing dimension		mm	880*290*220	880*290*220
Accessory gross weight		kg	5	5